

## TECHNICAL INFORMATION

Content	PVC-Free Olefin Composite
Weight (oz/lineal yard)	33
Thickness (inches)	0.034
Width (inches)	52-54
Meets or exceeds Type II physical testing	W 101, CCC-W-408D
Taber Scratch @ 11 ft-lbs. (GMW 14698)	No visible scratch
Fire Safety (ASTM E-84)	Class A
CAN/ULC S102	Pass
Indoor Air Quality CA01350	Pass
Abrasion Resistance (loss %) ASTM D-4060	< .05%
Impact resistance (in-lbs./f) ASTM D-5420	115
Tear Resistance MD/CD (grams) ASTM D-1922	> 3200 grams
Breaking StrengthB MD/CD (lbs.) ASTM D-751	130 / 100
Stain Resistance (ASTM D-1308)	13
Chemical Resistance (ASTM D-1308)	

### 11

- High performance heavyweight drill woven fabric backing
- Printed with water-based inks
- 30% post-industrial recycled content
- Supports LEED® v4.1 Criteria
- Phthalate free | Heavy metal free | Flame retardant additive free
- Antimicrobial free
- Formaldehyde free
- PFAS, PFOA and PFDE free.
- Health Product Declaration (HPD)
- Proposition 65 Compliant
- LBC Red List Chemical free
- Meets Healthier Hospitals Safer Chemicals guidance (HHI)
- Bleach cleanable 1:10 Bleach/Water Ratio (see cleaning instructions for more information)
- Disinfectant safe